

CS 405/505 FINAL EXAM SAMPLE QUESTIONS (SOLUTIONS)

1. True or False. A virtual method table is needed only for the execution of polymorphic functions in C++, but is not needed in Java.

False. A virtual method table is also needed for Java since all Java methods are potentially polymorphic.

2. List and briefly describe four (4) components of an activation record.

local variables of the subprogram

formal parameters of the subprogram

dynamic link - pointer to previous activation record

static link - pointer to activation record of static parent

return address - place to return to in caller code

return value - if subprogram is a function

3. Consider the Pascal array declaration:

A : array [-10 .. 10, -5 .. 5, 1 .. 10] of T;

Assuming that T requires 10 bytes of storage and A is stored at relative location 100, what is the relative location of A [1, 1, 2]?

$\text{addr}(A[1, 1, 2]) = \text{addr}(A) + (((1 - (-10)) * 11) + (1 - (-5))) * 10 + 2 - 1) * 10 = 100 + ((11 * 11 + 6) * 10 + 1) * 10 = 12,810$

4. Define the terms *dangling reference*, *garbage*, and *memory leakage*. Describe how each is created in a program and a possible solution to each.

See textbook.

5. Consider the following Pascal program:

```
program MAIN;
  var U, V : INTEGER;
  procedure A;
    var Y : INTEGER;
    ... (* point 4 *)
  end;
  procedure B;
    var U, V, Y : INTEGER;
    procedure C;
      ...
      begin
        ... (* point 3 *)
        A;
        ...
      end;
    begin (* B *)
      ... (* point 2 *)
      C;
      ...
    end;
  begin (* MAIN *)
    ... (* point 1 *)
    B;
    ...
  end.
```

Indicate which activation records are stacked at each of points 1, 2, 3 and 4 in the program as well as the exact contents of those activation records. Assuming static scoping, show the contents of the display at each of these points. Assuming dynamic scoping, what is the scope of V at point 4?

Static scoping

- 1) ARS = MAIN; DS = MAIN
- 2) ARS = MAIN, B; DS = MAIN, B
- 3) ARS = MAIN, B, C; DS = MAIN, B, C
- 4) ARS = MAIN, B, C, A; DS = MAIN, A

Note: ARS is the activation record stack, DS is the display stack.

With dynamic scoping, V belongs to B at point 4.

6. Consider the functions below in C++-like pseudocode.

```

int I;

int F (int X, int Y) {
    I = 2;
    Y = 1;
    return X + Y;
}

void main (void) {
    int A [3];
    A [0] = 7; A [1] = 11; A [2] = 13;
    I = 0;
    cout << F (A [I], I);
}

```

Show the values stored in the **locations** named A [0], A [1], A [2], I, X and Y at the entry and exit points of function F assuming (a) call by value, (b) call by reference, (c) call by value-result, and (d) call by name? Also, show the result which gets printed in each case.

The following table shows the results for each calling method.

Call by	A[0] i	A[0] o	A[1] i	A[1] o	A[2] i	A[2] o	I i	I o	X i	X o	Y i	Y o	Res
value	7	7	11	11	13	13	0	2	7	7	0	1	8
reference	7	7	11	11	13	13	0	1	a1	a1	a2	a2	8
value-result	7	7	11	11	13	13	0	1	7	7	0	1	8
name	7	7	11	11	13	13	0	1	t1	t1	t2	t2	12

a1 - addr (A [0])

a2 - addr (I)

t1 - thunk (A [I])

t2 - thunk (I)

Assuming all parameters are passed by reference, does *aliasing* occur in this program? If so, where?

Aliasing does occur in F as I may be referred to by its own name or by formal parameter Y.